

<p>Aggregate Industries IMS dept Bardon Hall, Copt Oak Road, Markfield, Leicestershire, LE67 9PJ</p>	<p>Safety Data Sheet Issue Date: July 2009</p>
<p>1. IDENTIFICATION OF THE SUBSTANCE</p>	<p>2. COMPOSITION / INFORMATION ON INGREDIENTS</p>
<p>Bituminous Road Materials</p> <p><u>Product description</u></p> <p>Bituminous road materials comprise of coated macadam, asphalts and other proprietary products that can be supplied hot or cold for surfacing, resurfacing and top dressing of public and private roads.</p>	<p>Bituminous road material is a mixture of:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Aggregate <input type="checkbox"/> Sand <input type="checkbox"/> Filler <input type="checkbox"/> Bitumen <input type="checkbox"/> Additives. <p>Aggregate, sand and filler are inert minerals. Bitumen is a high molecular hydrocarbon derived from crude oil distillation, which bonds the other ingredients into a homogenous stable material.</p> <p>Fluxing oil, of petroleum origin, paper fibres, latex, pigment, none inert fillers i.e. ash and other additives may be included in proprietary products.</p> <p>Note: Although this sheet covers new bituminous road materials, recycled products may also be utilised for some applications and in which case unknown compounds may be incorporated within the mix during the recovery process.</p>
<p>3. HAZARDS IDENTIFICATION</p>	<p>4. FIRST AID MEASURES</p>
<p>Hot bitumen burns.</p> <p>In confined or semi-confined spaces prolonged inhalation of high vapour concentrations could be a risk to health. Inhalation of bituminous material fume during work in the open air is unlikely to be of sufficient concentration to provide a health risk.</p> <p>Bitumen and fluxing oils may cause chemical burns and, following prolonged skin exposure, warts. If personal cleanliness is ignored this may lead to more serious skin conditions.</p> <p>If the product is colour pigmented, it may contain polycyclic aromatic hydrocarbons. Although bound in the product, some may cause skin cancer and are, therefore, classified as category 3 carcinogens.</p>	<p><u>General</u></p> <p>Where injury arises from contact with hot bituminous material rest, keep warm and obtain medical attention.</p> <p><u>Inhalation</u></p> <p>Remove immediately into the fresh air, rest, keep warm and obtain medical attention.</p> <p><u>Skin</u></p> <p>Wash with cold water and remove with a vegetable oil under medical supervision. Do not remove cloths that are adhering to the skin.</p> <p><u>Eyes</u></p> <p>Irrigate with cold water for 10 minutes and obtain medical attention.</p> <p><u>Ingestion</u></p> <p>Give water to drink, but do not induce vomiting, and obtain medical attention.</p>

<p>Aggregate Industries IMS dept Bardon Hall, Copt Oak Road, Markfield, Leicestershire, LE67 9PJ</p>	<p>Safety Data Sheet Issue Date: July 2009</p>
<p>5. FIRE FIGHTING MEASURES</p> <p><u>Suitable extinguishing media</u></p> <p>Dry powder and foam.</p> <p><u>Unsuitable extinguishing media</u></p> <p>CO2 and water - water jets must not be used, water fog can be used to cool exposed surfaces but only by personnel trained in fire fighting.</p> <p><u>Special exposure hazards in fire</u></p> <p>Hydrocarbon fumes may be released.</p> <p><u>Special protective equipment for fire-fighters</u></p> <p>Full protective clothing including suitable respirator or breathing apparatus.</p>	<p>6. ACCIDENTAL RELEASE MEASURES</p> <p><u>Personal precautions</u></p> <p>Wear overalls and gloves.</p> <p><u>Environmental measures</u></p> <p>Entry into watercourses should be avoided. Near water systems, materials should be stored in a dry area free from the risk of chemical contamination or fire.</p> <p><u>Method of cleaning</u></p> <p>Spillages of hot material onto roads and other surfaces should be cleared promptly before setting using appropriate mechanical methods.</p> <p>Bitumen may be removed from road making tools and machinery using a proprietary tar and bitumen remover, normally a hydrocarbon solvent. However, this method is not suitable for removal of bitumen from already macadamed surfaces. Reference should also be made to the supplier's safety data sheet prior to use to ensure adequate health, safety and environmental protection measures are employed.</p>
<p>7. HANDLING AND STORAGE</p> <p><u>Handling</u></p> <p>The product should be handled in a manner so as to minimise contact with the skin and eyes and to avoid prolonged inhalation of the fume.</p> <p><u>Storage</u></p> <p>Hot material is normally used upon receipt. Cold mixed or extended life materials should be stored in a secure, clean, dry area free from the risk of chemical contamination.</p>	<p>8. EXPOSURE CONTROLS/PERSONAL PROTECTION</p> <p><u>Workplace Exposure Limits</u></p> <ul style="list-style-type: none"> <input type="checkbox"/> Bitumen fume (listed as asphalt, petroleum fume): <input type="checkbox"/> Long-term exposure limit (8-hour TWA reference period) 5 mg/m3 <input type="checkbox"/> Short term exposure limit 15-minute reference period) 10 mg/m3 <p>Note: The above WELs are as published in EH40 2005</p> <p><u>Prevention measures</u></p> <p>Ensure good ventilation of all areas in which bituminous products are stored and used.</p> <p><u>Respiratory protection</u></p> <p>Respirators should be worn if fumes are likely to be present in significant quantities.</p> <p><u>Protection of skin and eyes</u></p> <p>Impervious gloves and overalls should be worn and eye protection is recommended.</p>

<p>Aggregate Industries IMS dept Bardon Hall, Copt Oak Road, Markfield, Leicestershire, LE67 9PJ</p>	<p>Safety Data Sheet Issue Date: July 2009</p>
<p>9. PHYSICAL & CHEMICAL PROPERTIES</p>	
<p><u>Appearance</u> Black, coated roadstone</p> <p><u>Other chemical properties</u> See Composition/Information on Ingredients above</p>	
<p>10. STABILITY AND REACTIVITY</p>	<p>11. TOXICOLOGICAL INFORMATION</p>
<p><u>Conditions to avoid</u> Temperatures above 230 °C</p> <p><u>Materials to avoid</u> May react with strongly oxidising materials</p> <p><u>Hazardous decomposition products</u> Toxic fumes and dark smoke will be produced in a fire situation.</p>	<p><u>Description of toxicological properties</u> Toxicity following a single exposure (orally, dermally or by inhalation) to bituminous products is of a low order. When bituminous products contain polycyclic aromatic hydrocarbons they are classified as category 3 carcinogens. With the use of good occupational and hygiene practices any risk will be minimal.</p>
<p>12. ECOLOGICAL INFORMATION</p>	<p>13. DISPOSAL CONSIDERATIONS</p>
<p><u>Environmental assessment</u> Where used and disposed of as intended (see Accidental Release Measures) no adverse environmental effects are foreseen.</p>	<p><u>Handling of any residues/waste products</u> Waste bituminous road materials may be recycled where appropriate facilities exist. However, if they are to be disposed of to landfill, reference should be made to the relevant waste management legislation including the requirements of the Hazardous Waste Regulations 2005 and the associated Waste Acceptance Criteria.</p>
<p>14. TRANSPORT INFORMATION</p>	<p>15. REGULATORY INFORMATION</p>
<p><u>Special carriage precautions</u> Not applicable, however, it is recommended that loads are kept secured and covered prior to use</p>	<p>Under the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP 3) the Danger Classification for bituminous products is:</p> <p><input type="checkbox"/> Irritant (+hazard symbol)</p> <p>In addition the following risk and safety phrases are applicable:</p> <p><input type="checkbox"/> R38: Irritating to skin <input type="checkbox"/> R41: Risk of serious damage to eyes. <input type="checkbox"/> R43: May cause sensitisation by skin contact. <input type="checkbox"/> S24: Avoid contact with skin. <input type="checkbox"/> S25: Avoid contact with eyes. <input type="checkbox"/> S26: If contact with eyes, rinse immediately with clean water and seek medical advice.</p>

<p>Aggregate Industries IMS dept Bardon Hall, Copt Oak Road, Markfield, Leicestershire, LE67 9PJ</p>	<p>Safety Data Sheet Issue Date: July 2009</p>
<p>16. OTHER INFORMATION</p>	
<p><u>Training advice</u></p> <p>Wear and use PPE</p> <p><u>Recommended uses</u></p> <p>Public and private road surfacing and resurfacing</p> <p><u>Further information sources</u></p> <p>Aggregate Industries UK Limited Bardon Hall, Copt Oak Road, Markfield, Leicestershire, LE67 9PJ</p> <p>Tel. (01530) 816600</p> <p><u>Sources of key data used to compile data sheet</u></p> <p>EH40 2005 Workplace Exposure Limits PPE Regulations 1992 COSHH Regulations 2002 (as amended) COSHH (Amendment) Regulations 2004 CHIP Regulations 2002 Environmental Protection Act 1990, Part II Hazardous Waste Regulations 2005</p>	<p>LEGAL NOTICE</p> <p>The information contained in this Safety Data Sheet was considered the best available at the date of issue. However, no warranty is made or implied that the information is accurate or complete. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.</p>
<p><u>Conditions to avoid</u></p> <p>Temperatures above 230 °C</p> <p><u>Materials to avoid</u></p> <p>May react with strongly oxidising materials</p> <p><u>Hazardous decomposition products</u></p> <p>Toxic fumes and dark smoke will be produced in a fire situation.</p>	<p><u>Description of toxicological properties</u></p> <p>Toxicity following a single exposure (orally, dermally or by inhalation) to bituminous products is of a low order. When bituminous products contain polycyclic aromatic hydrocarbons they are classified as category 3 carcinogens. With the use of good occupational and hygiene practices any risk will be minimal.</p>
<p>12. ECOLOGICAL INFORMATION</p>	<p>13. DISPOSAL CONSIDERATIONS</p>
<p><u>Environmental assessment</u></p> <p>Where used and disposed of as intended (see Accidental Release Measures) no adverse environmental effects are foreseen.</p>	<p><u>Handling of any residues/waste products</u></p> <p>Waste bituminous road materials may be recycled where appropriate facilities exist. However, if they are to be disposed of to landfill, reference should be made to the relevant waste management legislation including the requirements of the Hazardous Waste Regulations 2005 and the associated Waste Acceptance Criteria.</p>
<p>14. TRANSPORT INFORMATION</p>	<p>15. REGULATORY INFORMATION</p>
<p><u>Special carriage precautions</u></p> <p>Not applicable, however, it is recommended that loads are kept secured and covered prior to use</p>	<p>Under the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP 3) the Danger Classification for bituminous products is:</p> <p><input type="checkbox"/> Irritant (+hazard symbol)</p>

	<p>In addition the following risk and safety phrases are applicable:</p> <ul style="list-style-type: none"><input type="checkbox"/> R38: Irritating to skin<input type="checkbox"/> R41: Risk of serious damage to eyes.<input type="checkbox"/> R43: May cause sensitisation by skin contact.<input type="checkbox"/> S24: Avoid contact with skin.
--	--