

AGGREGATE INDUSTRIES

Specialist silica sands

Levenseat ProGolf 25™



A medium fine washed silica sand.

Applications

- Top dressing/amelioration sand/rootzone sand

Sectors

- Sports and leisure

Available in

- Loose: bulk tipplers
- Bulk bags (tote)

Description

Levenseat ProGolf 25 specialist silica sand is extremely popular for use as a medium fine top dressing, rootzone sand or where a medium fine amelioration option is required. Levenseat's unique production process ensures that ProGolf 25 has a market leading medium fine percolation rate.

Levenseat specialist sands are tried and tested with market-leading quality, consistency across a complete range of products and applications.

Mechanical analysis

Sieve size (mm)	Typical grading % retained	Description
2 to 5	0	Fine gravel
1 to 2	0.8	Very coarse sand
0.5 to 1	17.5	Coarse sand
0.25 to 0.5	50.2	Medium sand
0.15 to 0.25	30.6	Fine sand
0.05 to 0.15	0.7	Very fine sand
<0.05	0.2	Silt plus clay

Saturated hydraulic conductivity	1041mm/hr
Specific gravity	2.69 Mg/m ³
Uncompacted bulk density	1.49 t/m ³
Nominal effective size	0.16-0.38mm
Uniformity coefficient	<2.3mm



*tested at 30cm tension

NOTE:

Gradation figures stated are indicative value, for specific grading values please contact Aggregate Industries Technical Department.

Sand is a naturally occurring product, therefore colour may vary.

Levenseat ProGolf 25 washed silica sand

Source:	Levenseat Quarry, West Lothian
Geology:	Carboniferous sandstone
Composition:	Quartz
Grain shape:	Sub-angular
Sphericity:	Medium



Levenseat ProGolf 25™

Sustainability and local sourcing

Energy use: Aggregate Industries is at the forefront of sustainability and has committed to reduce carbon emissions by 20% by 2016 based on a 2012 base line.

Recyclable: 100% of the product can be recycled thus reducing the amount of material that is sent to landfill.

Manufacturing location: produced in the the UK, with locally sourced materials under strict environmental and social legislation, for local supply.

Policies

Aggregate Industries' policies on the environment and community, health and safety and sustainable solutions for different product applications can be viewed on our website www.aggregate.com

COSHH data

Full COSHH data on Levenseat Specialist Sands products is available on request. Please call 01698 870970 for more information.

Technical support

Further information and technical guidance is available through the sales office.

Please call Levenseat Specialist Sands technical services on 01698 870970.

We can design products around your specific requirements. Please contact our technical department on 01698 870 970 for more information.

Levenseat Specialist Sands, Levenseat Quarry,
Fauldhouse, West Lothian EH47 9AD.

T: 01698 870970
E: levenseat@aggregate.com
W: www.aggregate.com

