

RAPID SET CEMENT

Lafarge Rapid Set Cement is a quality-assured rapid hardening Portland cement for applications requiring strong, durable cement.

GENERAL INFORMATION

Lafarge Rapid Set Cement is a Portland cement containing calcium aluminate for rapid hardening.

FEATURES


- Strong, durable, high quality finish in a fraction of the time compared with standard cement.
- Sets within 1 hour. Foot traffic within 4 hours and vehicle traffic within 12 hours.

APPLICATIONS

Rapid Set Cement used for laying bricks and blocks.

- Concrete
- Render
- Screed

IDEAL FOR:



CONCRETING

FLOOR SCREEDING

RENDERING

AVAILABILITY

Available in 25kg paper bags.

STORAGE

- Rapid Set Cement should be stored unopened in cool conditions and should be stacked in a safe and stable manner.

CONDITIONS OF USE:

- The final strength and finish of this product will depend on the user having the necessary skills and knowledge of the product and its application.
- Lafarge cannot be held responsible where workmanship has not been carried out in accordance with good practice.
- Manual handling should comply with The Manual Handling Operations Regulations 1992.
- For optimum performance, it is essential that mixes containing Rapid Set Cement should not dry out too quickly. Adequate curing is achieved by protecting the material from adverse weather conditions until fully hardened.
- Rapid Set Cement may be used in the range of traditional nominal mixes as for traditional Portland cement.
- To achieve optimum performance from Rapid Set Cement in concrete or other products, it is essential that it is correctly specified and used.
- As with other cements in building work, there is no substitute for good site practice. It is essential to use the correct materials, proportion and mix the materials properly, add the correct amount of water, compact, cure and protect as appropriate.
- Normal hot and cold weather practice should also be followed.

TECHNICAL SUPPORT

Should you require information for this or any other product within the Lafarge range, please contact our Customer Support team on 01285 646900 or visit our website at:

www.lafargecement.co.uk

HEALTH AND SAFETY

Contact between cement powder and body fluids (e.g. eye fluids) may cause irritation, dermatitis or burns. Cement is classified as an irritant under the Chemicals (Hazard information and Packaging) Regulations. Please refer to the product safety data sheet for full information.

